



PRODUCT NAME:

EVERBUILD 406 STABILISING SOLUTION

PRODUCT CODE/S:

EB406STAB/ EB406STABILISING

OVERVIEW

EVERBUILD 406 STABILISING SOLUTION IS A SOLVENT-BASED SURFACE PRIMER SPECIFICALLY FORMULATED TO STABILISE AND SEAL FRIABLE, POROUS, OR POWDERY SUBSTRATES. IT WORKS BY DEEPLY PENETRATING THE SURFACE TO BOND LOOSE PARTICLES AND CREATE A SOUND BASE FOR SUBSEQUENT DECORATION OR RENDERING.

406 IS SUITABLE FOR USE ON PLASTER, RENDER, CONCRETE, BRICKWORK, AND MOST MASONRY SURFACES. IT IS PARTICULARLY USEFUL FOR WEATHERED OR CHALKY EXTERIORS WHERE PAINT MAY OTHERWISE FAIL TO ADHERE PROPERLY. ONCE CURED, IT PROVIDES AN EXCELLENT KEY FOR WATER-BASED OR SOLVENT-BASED TOPCOATS.

DETAILS:

Key Features:

- Deeply penetrates and seals dusty, porous, or powdery surfaces
Ideal for use before painting or wallpapering
Suitable for interior and exterior applications
Improves adhesion of paints and coatings
Reduces absorbency of porous substrates
Fast drying
Solvent-based for superior bonding

Application Area

Stabilising old or chalky masonry and render
Priming porous concrete before painting
Binding dusty plaster or screed
Preparing exterior walls for decoration
Ensuring paint adhesion on aged or degraded surfaces

Technical Specifications

Base Type: Solvent-based
Colour: Clear (dries transparent)
Pack Sizes Available: 1L, 2.5L, 5L (most commonly 5L)
Coverage: Approximately 5–10 m² per litre (varies by surface)
Drying Time: Touch dry in 2–4 hours (depending on temperature & humidity)
Recoat Time: 12–24 hours for best results
Application Method: Brush or roller
Flashpoint: >23°C
VOC Content: High (solvent-based product)
Shelf Life: 24 months unopened (store in a cool, dry place)

STANDARDS

EN ISO 12944-4