

# DATA SHEETS



# **PRODUCT NAME:**

ALCON GENERAL PURPOSE CLEAR SILICONE 285ML

## **PRODUCT CODE/S:**

#### EBGPGALCON

#### **KEY FEATURES:**

ALCON GENERAL PURPOSE CLEAR SILICONE IS A VERSATILE, ACETOXY-CURE SILICONE SEALANT THAT OFFERS EXCELLENT ADHESION TO MOST NON-POROUS MATERIALS. IT PROVIDES A FLEXIBLE, WEATHER-RESISTANT SEAL THAT'S SUITABLE FOR BOTH INDOOR AND OUTDOOR USE. THIS SILICONE IS PERFECT FOR SEALING AROUND GLASS, CERAMIC TILES, SANITARY FITTINGS, AND WINDOWS. THE CLEAR FINISH ENSURES A CLEAN, PROFESSIONAL

CLEAR FINISH FOR INVISIBLE JOINTS
WATERPROOF AND PERMANENTLY FLEXIBLE
GOOD ADHESION TO GLASS, CERAMICS, ALUMINIUM, AND OTHER NON-POROUS
SURFACES
MOULD-RESISTANT – SUITABLE FOR BATHROOMS AND KITCHENS
SUITABLE FOR INTERIOR AND EXTERIOR USE

EASY TO APPLY AND SMOOTH

### **DETAILS:**

# **TECHNICAL SPECS:**

Type: Acetoxy silicone sealant Curing System: Moisture cure Colour: Clear Packaging: 285ml cartridge Skin Time: ~10 minutes (@ 20°C) Full Cure: ~2mm per 24 hours Application Temperature: +5°C to +40°C Service Temperature: -40°C to +150°C Movement Capability: ±12.5%

#### **IDEAL FOR:**

Sealing around windows and door frames

General glazing work

Kitchen and bathroom sealing

DIY home repairs

Sanitary joints - sinks, showers, tiles

Draught-proofing around fittings

#### **INSTRUCTION FOR USE:**

Prepare Surfaces:
Surfaces must be clean, dry, and free of dust, grease, and old sealant.
Apply the Sealant:
Cut the tip of the cartridge and attach the nozzle.
Apply using a standard caulking gun.

Smooth with a wet finger or tooling tool within 5–10 minutes. Curing:

Avoid water contact until fully cured (approx. 24 hours for 2mm). Clean tools and excess sealant immediately with white spirit.

**STANDARDS** 

# EN 15651-1

sales@abcabrasives.ie

01 8486088