

# DATA SHEETS



## **PRODUCT NAME:**

FLAP WHEELS

### **PRODUCT CODE/S:**

FW3005120, FW301040, FW301080, FW4015120, FW502040, FW6015120, FW6030120, FW6040120, FW6140, FW62120

## **KEY FEATURES:**

Abrasive wheels suitable to be used as sanding wheels for electric drills, cordless drills, die grinders  $High \ quality \ aluminum \ oxide \ coated \ abrasive \ cloth \ provides \ a \ solid \ and \ durable \ grinding \ power$ combined with high efficiency.


 $Wheel \, can \, remove \, paint \, and \, sand, \, grind, \, level, \, and \, strip \, surfaces \, and \, makes \, quick \, work \, of \, it. \, These \, it is a surface and \, remove \, paint \, and \, sand, \, grind, \, level, \, and \, strip \, surfaces \, and \, makes \, quick \, work \, of \, it. \, These \, it is a surface \, and \, remove \, paint \, and \, sand, \, grind, \, level, \, and \, strip \, surfaces \, and \, makes \, quick \, work \, of \, it. \, These \, it is a surface \, and \, remove \, paint \, and \, sand, \, grind, \, level, \, and \, strip \, surfaces \, and \, makes \, quick \, work \, of \, it. \, These \, it is a surface \, and \, remove \, paint \, and \, sand, \, grind, \, level, \, and \, strip \, surfaces \, and \, makes \, quick \, work \, of \, it. \, These \, it is a surface \, and \, remove \, paint \, and \, sand, \, grind, \, gr$ wheels style disks make use easy.

 $Widely\,used\,for\,flap\,sander\,wheels\,for\,the\,stripping\,of\,old\,layers\,of\,paint\,, during\,resurfacing\,project,$ sanding, finishing contoured wood surfaces, clean up welds and cuts in iron, stainless steel and metal alloys.

#### **MATERIAL:**

BONDING AGENT RESIN, ALUMINIUM OXIDE

# **SIZE CHART**



| CODE      | HEIGHT X DIA | GRIT | GRADE  |
|-----------|--------------|------|--------|
| FW3005120 | 30MM X 5mm   | 120  | COARSE |
| FW301040  | 30mm X 10mm  | 40   | FINE   |
| FW301080  | 30mm X 10mm  | 80   | COARSE |
| FW4015120 | 40mm X 15mm  | 120  | MEDIUM |
| FW502040  | 50mm X 20mm  | 40   | FINE   |
| FW6015120 | 60mm X 15mm  | 120  | COARSE |
| FW6030120 | 60mm X30mm   | 120  | MEDIUM |
| FW6040120 | 60mm X 40mm  | 120  | FINE   |
| FW6140    | 165mm X 25mm | 40   | COARSE |
| FW62120   | 165mm X 50mm | 120  | FINE   |

#### **STORAGE**

IT IS RECOMMENDED THAT ALL COATED ABRASIVE PRODUCTS SHOULD BE STORED AT CONSTANT LEVELS OF TEMPERATURE AND HUMIDITY WITHIN THE RANGES OF 18-22°C, 50-65% RH. THEY SHOULD BE KEPT AWAY FROM DAMP (OR COLD) WALLS, WINDOWS OR FLOORS TO AVOID POSSIBLE MOISTURE ABSORPTION. EQUALLY STORAGE ADJACENT TO HEAT SOURCES E.G. STEAM PIPES, RADIATORS, HOT AIR DUCTS, OVENS, ETC.,





















