


PRODUCT NAME:

PAINTERS CAULK WHITE

PRODUCT CODE/S:

 PC380
PC310

KEY FEATURES:

SAFELINE PAINTERS CAULK IS A HIGH-QUALITY, FLEXIBLE SEALANT IDEAL FOR INTERIOR APPLICATIONS WHERE A SMOOTH, PAINTABLE FINISH IS REQUIRED. IT'S DESIGNED TO FILL GAPS, CRACKS, AND JOINTS BETWEEN MATERIALS SUCH AS PLASTER, WOOD, CONCRETE, AND MORE. IT HAS EXCELLENT ADHESION TO MOST SURFACES AND DRIES QUICKLY, ALLOWING FOR PAINTING WITHIN A SHORT PERIOD.

- **FLEXIBLE:** REMAINS FLEXIBLE AFTER CURING, ENSURING DURABILITY AND CRACK RESISTANCE OVER TIME.
- **QUICK-DRYING:** PAINTABLE WITHIN 1-2 HOURS OF APPLICATION.
- **EASY APPLICATION:** READY-TO-USE CAULK IN A CONVENIENT 380ML CARTRIDGE FOR CAULKING GUNS.
- **SMOOTH FINISH:** ENSURES A NEAT, PROFESSIONAL APPEARANCE ONCE DRIED.
- **EXCELLENT ADHESION:** BONDS WELL WITH A VARIETY OF SURFACES INCLUDING WOOD, PLASTER, MASONRY, AND BRICK.
- **SHRINK AND CRACK RESISTANT:** WON'T SHRINK OR CRACK, PROVIDING A LONG-LASTING

DETAILS:
TECHNICAL SPECS:

Base	Acrylic emulsion
Appearance	Smooth paste
Color	White
Packaging	380ml / 310ml cartridge
Skin Forming Time:	10-30 minutes (at 23°C and 50% RH)
Curing Time	24 hours (depending on thickness, temperature, and humidity)
Paintability:	Paintable after 1-2 hours (depending on environmental conditions)

IDEAL FOR:

- Filling gaps around door and window frames.
- Sealing baseboards, crown molding, and trim joints.
- Interior crack repairs on plaster, drywall, or wood.
- Areas that require painting for a seamless finish.

INSTRUCTION FOR USE:

- Ensure surfaces are clean, dry, and free from dust or loose material.
- Cut the nozzle to the desired size and apply using a caulking gun.
- Smooth with a damp cloth or caulking tool within 5-10 minutes of application.
- Allow to dry for 1-2 hours before painting over.

STANDARDS