



PRODUCT NAME:

FLAMINGO 450ML SPRAY PAINT

PRODUCT CODE/S:

| | |
|----------------------|-------------------------------|
| SP1001 - BLACK GLOSS | SP1008 - BLACK MATT |
| SP1002 - WHITE GLOSS | SP1014 - YELLOW GLOSS |
| SP1005 - GREEN GLOSS | SP1021 - HIGH TEMP BLACK MATT |
| SP1006 - BLUE GLOSS | SP1028 - SILVER ZINC |
| SP1007 - WHITE MATT | SP1029 - SATIN BLACK |

KEY FEATURES:

WIDELY USED IN ADVERTISING INDUSTRY, SURFACE-TREATED WOOD, METAL, ABS PLASTIC, GLASS AND AUTOMOTIVE, MOTORCYCLE SURFACE DECORATION AND PROTECTION. SPRAY PAINT HAS THE FEATURES OF GOOD LEVELING, HIGH COVERAGE, FAST DRY, RICH COLOR AND HIGH LUSTER, BETTER FLEXIBILITY, IMPACT ENDURING, STRONG ADHESIVENESS, AND MATCH WELL WITH MANY TYPES OF PAINT PRIMERS. IT'S FAST-DRYING AND SCRATCH-RESISTANT, AND WILL NOT FADE OR YELLOW. IT ALSO PROTECTS AGAINST RUST

DETAILS:



APPLICATION:

It is used for cleaning switched off electrical equipment, such as motors, contactors, coil, relays, switches, connections, circuits breakers, plugs and jacks, generators, electrical & electronic contacts, PCB's, precision electronic and optical equipment.

USAGE DIRECTION:

1. Completely remove the place for spraying of the oil, water and dust.
2. Before spraying, shake the bottle for about two minutes, and to make the paint fully mixed evenly.
3. Press the top with a finger and evenly spray the surface to and from at a distance of 20-30 cm.
4. By spraying more times, every two minutes to spray a thin layer can get the better effect.
5. Invert the bottle then spray it several times after use to avoid clog valve.

STANDARDS

