



PRODUCT NAME:

ECOABSORBER DA-1S LANYARD 2M

PRODUCT CODE/S:

031144

KEY FEATURES:

Key Features

High-Strength Webbing – Constructed from premium polyester webbing for exceptional durability and load-bearing capacity.

Optimal Length (2.0M) – Provides the perfect balance between mobility and safety, reducing fall risks.

Shock-Absorbing Design (if applicable) – Can be integrated with an energy absorber to minimize fall impact forces.

Heavy-Duty Stitching – Reinforced stitching enhances strength and reliability under tension.

Corrosion-Resistant Metal Components – Equipped with high-quality steel or aluminum connectors for long-lasting performance.

Lightweight and Flexible – Designed for ease of movement without compromising safety.

Certified for Safety Compliance – Meets EN 354:2010 and other international safety standards.

DETAILS:

Product Overview

The 1.4M Webbing Lanyard is a high-quality, durable safety lanyard designed for secure attachment in fall protection systems. It provides a reliable connection between a worker's harness and an anchor point, ensuring safety while working at height. Manufactured from heavy-duty webbing material, this lanyard is built for superior strength, flexibility, and resistance to wear, making it an essential component in scaffolding, construction, and industrial applications.

Technical Specifications

Material: High-strength polyester webbing

Length: 1.4 meters

Width: 25-45mm webbing (depending on model)

Breaking Strength: Minimum 22 kN

Connectors: Steel/aluminum hooks with automatic locking system (depending on configuration)

Color: High-visibility design for easy identification

Compliance: EN 354:2010, ANSI Z359.3, CE certified

Applications

Construction and scaffolding work

Roofing and industrial maintenance

Tower climbing and wind energy sector

Warehouse and logistics safety systems

Confined space operations

STANDARDS

 EN 361:2002